

The Pro's Choice Since 1936

SAKRETE®

Concrete Bonder & Fortifier

PRODUCT # 18616, 18564

SAKRETE® Bonder & Fortifier may be used as either a paint-on bonder (straight from the bottle) or as a fortifier/ admixture (mixed 1:1 with water). When used as a bonder, it improves the bond between new and old concrete. Fortifier/admixture: When used as a fortifier/admixture, it improves tensile and flexural strength, resistance to water penetration and freeze/thaw damage, reduces shrinkage and the need for wet curing, as well as improving the bond strength.

SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. WARNING: Wear protective clothing and equipment. See HMIS block. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

PREPARATION:

Area to be resurfaced should be structurally sound. Clean the area thoroughly removing all dirt, oil, grease, paint and loose material. Dampen the area to be resurfaced with water.

MIXING & USE:

Mix entire contents thoroughly before using. Do not shake. SAKRETE® Concrete Bonder & Fortifier can be used in two ways. Where improved resistance to water or chemical penetration or resistance to freeze/thaw damage are the primary concerns, use as a fortifier/admixture. Where improving bond strength is the main concern, use as a paint-on. For use as a paint-on bonder: Stir Bonder & Fortifier and apply with a paintbrush. Cover the area completely to insure proper bond. Bonder & Fortifier should be tacky to the touch during application of fresh patching material. Apply the prepared patching material and trowel to a smooth finish. For best results mix a slurry consisting of 2 parts Bonder & Fortifier with one part portland cement. Apply slurry with a paintbrush. Cover the area completely to insure proper bond. Bonder & Fortifier should be tacky to the touch during application of fresh patching material. Apply the prepared patching material and trowel to a smooth finish.

COVERAGE: (As a Primer)

Quart Size: 125 - 200 sq. ft. (12 - 19 sq. m.)

Gallon Size: 500 - 800 sq. ft. (46 - 74 sq. m)

Coverage will vary due to the porosity and texture of the substrate.

STORAGE:

Store in a tightly closed container. Keep from freezing.

PACKAGING:

1 Quart (0.95 L) - UPC: 7-64661-18616-8

1 Gallon (3.8 L) - UPC: 7-64661-18564-2

Not all sizes available in all areas

SHELF LIFE: One year from date of manufacture.

HMIS BLOCK

BONDER & FORTIFIER

HEALTH	3
FLAMMABILITY	0
REACTIVITY	1
PERSONAL PROTECTION	X

CAUTION: Vapors may cause irritation of eyes, nose and throat. May cause skin sensitization or other allergic responses. **HARMFUL IF SWALLOWED.** Do not breathe vapors. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Close container after each use. Do not transfer to unmarked container. **FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If vapors or fumes are inhaled, remove person to fresh air. If swallowed, give plenty of water and call a physician immediately. **DO NOT INDUCE VOMITING.**

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383
www.sakrete.com